



	型号 TYPE	尺寸 L*W*H(mm)	电感量 L	电流 I	工作温度范围 Operating temperature range	包装 Packaging
	CD32	3.5*3.0*2.1	1.0 μ H ~390 μ H	3.0A ~110mA	-25°C~+105°C	3000pcs/Reel ϕ 330mm
	DB0905	8.79*6.1*5.1	0.18 μ H ~47 μ H	10.0A ~0.72A	-40°C~+85°C	1500pcs/Reel ϕ 330mm
	CDRB0603	6.5*4.45*2.92	1.0 μ H ~2200 μ H	2.9A ~20mA	-25°C~+105°C	2500pcs/Reel ϕ 330mm
	PS4018	4.0*4.0*1.8	0.56 μ H ~3300 μ H	1.9A ~70mA	-40°C~+85°C	3000pcs/Reel ϕ 330mm
	CER318LX	3.3*3.3*2.0	1.2 μ H ~56 μ H	2.2A ~0.35A	-40°C~+105°C	1000pcs/Reel ϕ 180mm
	CER416CL	4.0*4.0*1.8	1.5 μ H ~39 μ H	1.4A ~0.26A	-40°C~+105°C	1000pcs/Reel ϕ 180mm
	CER520CL	5.3*5.3*2.0	1.0 μ H ~47 μ H	3.0A ~0.72A	-40°C~+105°C	2000pcs/Reel ϕ 330mm
	CER530CL	5.3*5.3*3.0	1.5 μ H ~100 μ H	3.5A ~0.4A	-40°C~+105°C	2000pcs/Reel ϕ 330mm
	CER620CL	6.2*6.2*2.0	1.0 μ H ~150 μ H	2.6A ~0.25A	-40°C~+105°C	2000pcs/Reel ϕ 330mm
	CER630CL	6.2*6.2*3.0	1.2 μ H ~270 μ H	3.6A ~0.26A	-40°C~+105°C	2000pcs/Reel ϕ 330mm
	CDRH5D28	6.0*6.0*3.0	2.5 μ H ~100 μ H	2.6A ~0.42A	-40°C~+105°C	2000pcs/Reel ϕ 330mm
	CER843DL	8.0*8.0*4.5	1.0 μ H ~1000 μ H	6.0A ~0.22A	-40°C~+105°C	1000pcs/Reel ϕ 330mm
	CDRH105	10*10*5	0.8 μ H ~1000 μ H	9.5A ~0.42A	-40°C~+105°C	500pcs/Reel ϕ 330mm
	CDH127	12*12*8	1.2 μ H ~1000 μ H	9.8A ~0.55A	-40°C~+105°C	500pcs/Reel ϕ 330mm



Power Inductors

	型号 TYPE	尺寸 L*W*H(mm)	电感量 L	电流 I	工作温度范围 Operating temperature range	包装 Packaging
 	SER106	10*10*6.5	0.22 μ H ~10 μ H	19A ~4.9A	-40°C~+125°C	450pcs/Reel Φ 330mm
 	PQ2014	22*14*17	3.3 μ H ~22 μ H	35A ~15A	-40°C~+125°C	box
 	SDF1212	12*11.3*9.7	0.22 μ H ~10 μ H	37A ~6A	-40°C~+105°C	300pcs/Reel Φ 330mm

*未列尺寸可以定制