



1) 外形尺寸 DIMENSIONS(mm)



2) 接线图 CONNECTION



3) 推荐焊盘 LAND PATTERN(mm)



A	B	C	D	a	b	c
2.5±0.2	2.0±0.2	1.0max	0.6±0.3	2.8	1.2	2.0

4) 电气规格 SPECIFICATIONS:

Part NO.	Inductance L (uH)	DCR(mΩ) Max	Saturation Current Isat (A)	Heating Rating Current Idc (A)
WDC252010JB-R22M	0.22±20%	12.5	7.2	5.3
WDC252010JB-R24M	0.24±20%	14	7.0	4.8
WDC252010JB-R33M	0.33±20%	26	6.0	4.0
WDC252010JB-R47M	0.47±20%	32	4.5	3.51
WDC252010JB-R68M	0.68±20%	54	3.87	3.06
WDC252010JB-1R0M	1.0±20%	49	3.15	2.7
WDC252010JB-1R5M	1.5±20%	91	2.34	2.25
WDC252010JB-2R2M	2.2±20%	119	2.16	2.07
WDC252010JB-4R7M	4.7±20%	262	1.62	1.22

记事 Note

- ① Isat: Inductance decrease by 30% from its value without current.
- ② Idc: The DC current at which the temperature rise is $\Delta T=40^{\circ}\text{C}$. ($T_a=25^{\circ}\text{C}$)
- ③ Inductance measuring condition: 1MHz/1mA
- ④ Operating temperature range: $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$ (including coil's self temperature rise)

*Packaging: 3000pcs/Reel, $\phi 180\text{mm}$, 5Reel/box

型号 TYPE	WDC252010JB	
---------	-------------	--